

WWW.DELOCK.COM



DATA SHEET

USB 2.0 > VGA Adapter

Description

The USB 2.0 to VGA Adapter enables you to connect any VGA monitor, LCD, projector to your PC or notebook with the system requirement as below, without need of a second graphics card. The USB2.0 SVGA adapter can mirror and enlarge the display. You can use up to 6 monitors depending on the system support. An extra adapter is required for each monitor.

We would like to point out that this adapter is suitable for simple applications and thus cannot replace a graphic card.

Images







Ref. 61931 EAN 4043619619313

Specification

- USB 2.0 specification
- VGA interface
- Resolution up to 1680 x 1050 at 32 Bit
- Max. resolution up to 2048 x 1280 (depend on the system)
- Up to 6 adapter per Computer useable
- Hot Plug, Plug & Play

System requirements

- Windows 2000/XP/Vista/Vista-64
- A free USB 2.0 port
- Minimum 512MB RAM
- VGA Graphics card with minimum 256MB memory
- Pentium 4, Athlon 2.6 GHz, or above

Package content

- USB 2.0 VGA adapter
- USB 2.0 cable
- Driver CD
- User manual

Package

• Blister

© 2010 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.